



TL09 Sign

Illuminated LED sign for decks, stores and engine rooms

Beispieltext

Technical Details

Possible combinations of features and other options available on request. Please contact us for more information.

Luminaire Type	Emergency Lighting
Input Voltage	230 VAC / 110 - 240 VAC / 24 VDC
Area	Indoor / Outdoor
Application	Cruise / Offshore / Naval / Commercial
Frequency	50-60 Hz / 0 Hz
Wattage	1x 4 W / 1x 6 W
Lumen Output	250 lm / 500 lm
Color Temperature	3000 K / 4000 K / 5700 K / 6500 K / Red / Green / Blue
Control Mode	Switchable / Dimmable / DALI
Emergency Function	Sec. circuit / 3h Battery backup
Cover / Diffusor	Polycarbonate opal / satin

Material of Housing	Galvanized steel / Stainless Steel 1.4404
Color of Housing / Ring	RAL / NCS colors
Type of Light Source	LED
Light Source Included	Yes
Cable Entry	Cable glands, Plastic / Brass, 1x-2x M20 / 1x-2x M25
External Wiring	Ø 6 - 13 mm / Ø 9 - 17 mm
Type of Connection	Terminal 3-pole / 5-pole, 2.5mm ² / 4mm ²
Mounting Type	Mounting holes
IP Class	IP67
Corrosion Class	C3L / CX VH
Ambient Temperature in °C	-25 ... +45
Features	Shock proof / EMI proof / Adaption light / Connection box

Images

