



DE38 L

Recessed mounted ceiling luminaire for accommodation and public areas

The **DE38L** from LightPartner is a recessed LED ceiling luminaire built for accommodation areas and public spaces. Its galvanized steel housing with a powder-coated finish ensures lasting durability, while the ice-crystal polycarbonate diffuser provides comfortable, glare-free illumination. Thanks to its practical clamp-mounting system, the DE38L can be installed quickly and securely in a wide variety of ceiling types, making it a highly adaptable solution for modern marine interiors. With options such as dimming, emergency backup, and alternative diffuser designs, it delivers reliable and versatile lighting tailored to demanding maritime standards.

Technical Details

Possible combinations of features and other options available on request. Please contact us for more information.

Luminaire Type	Ceiling Luminaire
Input Voltage	230 VAC / 120 VAC / 120-230 VAC / 24 VDC
Area	Indoor
Application	Cruise / Offshore / Naval / Commercial
Frequency	50-60 Hz / 0 Hz
Wattage	2x 17 W / 2x 22 W
Lumen Output	3100 lm / 4500 lm
Color Temperature	3000 K / 4000 K / 5700 K / 6500 K / Red / Green / Blue
CRI Color Rendering Index	80 / 90
Control Mode	Switchable / Dimmable / DALI
Emergency Function	Sec. circuit / 3h Battery backup
Cover / Diffusor	Clear polycarbonate with ice crystal / prismatic / opal / parabolic louver

Material of Housing	Galvanized Steel
Color of Housing / Ring	RAL / NCS colors
Type of Light Source	LED
Light Source Included	Yes
Cable Entry	1-4x Grommets / 1-4x Cable glands M20, Plastic / Brass
External Wiring	Ø 6 - 13 mm
Type of Connection	Terminal 3-pole / 5-pole, 2.5mm ² / 4mm ²
Internal Wiring	Through wired
Mounting Type	Bracket
IP Class	IP20/44
Ambient Temperature in °C	-20 ... +40 / -25 ... +45
Cut Out in mm	233x1250 mm
Features	B0 Execution / Shock proof/ EMI proof

Images

