

# DA25 S

Ceiling LED luminaire, surface mounting, for passage ways, cabins, lounges, accommodation areas and offices






The DA25 from LightPartner is an ultra-slim surface-mounted LED luminaire ideal for passageways, cabins, lounges, accommodation areas, and offices. Its elegant aluminum housing with a prismatic polycarbonate diffuser ensures gentle, uniform light across every surface, while the innovative mounting plate allows for completely tool-free installation—making it both practical and aesthetic. Designed to meet maritime classification standards, the DA25 delivers superb illumination with effortless setup, supported by options like high-output performance, dimming, alternative color temperatures, and even black-housing variants to fit diverse interior styles.

## Technical Details

Possible combinations of features and other options available on request. Please contact us for more information.

Luminaire Type	Ceiling Luminaire
Input Voltage	230 VAC / 120 VAC
Area	Indoor
Application	Cruise / Offshore / Commercial
Frequency	50-60 Hz
Wattage	1x 12 W / 1x 24 W
Lumen Output	1200 lm / 2400 lm
Color Temperature	3000 K / 4000 K
CRI Color Rendering Index	80
Control Mode	Switchable / Dimmable / DALI

Emergency Function	Optional Sec. circuit
Cover / Diffusor	Polycarbonate prismatic
Material of Housing	Aluminium
Color of Housing / Ring	RAL / NCS colors
Type of Light Source	LED
Light Source Included	Yes
Type of Connection	Connection cable with Wago 3-pole plug
Mounting Type	Mounting holes
IP Class	IP44
Ambient Temperature in °C	0 ... +45 / -20 ... +45

**Images**

[mm]