

SP66 M

Mirror luminaire, LED, for cabins, bathrooms, lavatories and accommodation areas





The **SP66M** from LightPartner is a mirror luminaire tailored for cabins, bathrooms, lavatories, and accommodation areas, combining maritime-grade reliability with sleek design. Its galvanized steel housing finished with a robust powder coating, complemented by white polycarbonate end caps and an opal structured diffuser, delivers clean and dependable lighting aligned with classification standards. Designed for practicality, it offers flexible installation with dual cable inlets and optional switch or socket configurations. Built with robust protection (IP44) and energy-efficient LED technology, the SP66M brings refined illumination and convenience to demanding shipboard environments.

Technical Details

Possible combinations of features and other options available on request. Please contact us for more information.

Luminaire Type	Wall Luminaire
Input Voltage	230 VAC / 120 VAC
Area	Indoor
Application	Cruise / Offshore / Naval / Commercial
Frequency	50-60 Hz
Wattage	1x 9 W
Lumen Output	1100 lm
Color Temperature	3000 K / 4000 K / 5700 K / 6500 K / Red / Green / Blue
CRI Color Rendering Index	80 / 90
Control Mode	Switchable / Integrated on-off switch
Cover / Diffusor	Polycarbonate opal, structured

Material of Housing	Galvanized Steel
Color of Housing / Ring	RAL / NCS colors
Type of Light Source	LED
Light Source Included	Yes
Cable Entry	2x Grommets
External Wiring	Ø 6 - 13 mm
Type of Connection	Terminal 3-pole / 5-pole, 2.5mm ²
Mounting Type	Mounting holes
IP Class	IP44
Ambient Temperature in °C	-25 ... +45
Features	2-pole Switch / Razor Socket

Images

[mm]

maintenance area

MB5.115.0041.00