

# DL110 Q

Adjustable downlight for accommodation and public areas



The **DL110Q** from LightPartner is a versatile LED downlight designed for cabins, public areas, and corridors aboard ships. Its sleek, black polycarbonate housing is paired with a decorative white powder-coated frame, delivering a clean, modern look. The light head rotates up to  $\pm 25^\circ$  and swivels through  $350^\circ$ , allowing precise beam orientation, and locks firmly in place. With high-efficiency LED modules at low power usage and warm 3,000 K light quality, the DL110Q balances comfort with performance. Easy to install in ceilings up to 20 mm thick using a swiveling insert and Wago 3-pole plug-in connection, the downlight is fully compliant with maritime classification standards. Available in configurations with one to three light modules to match lighting demands.

## Technical Details

Possible combinations of features and other options available on request. Please contact us for more information.

Luminaire Type	Downlight
Input Voltage	230 VAC
Area	Indoor
Application	Cruise / Offshore / Naval / Commercial
Frequency	50-60 Hz
Wattage	1x 13 W / 2x 13 W / 3x 13 W
Lumen Output	1200 lm / 2400 lm / 3600 lm
Color Temperature	2700 K / 3000 K / 4000 K
CRI Color Rendering Index	80 / 90
Beam Angle	15° / 24° / 40°
Beam Direction	Tilt- and turnable

Control Mode	Switchable / Dimmable
Material of Housing	Polycarbonate
Color of Housing / Ring	RAL / NCS colors / Chrome / Gold
Type of Light Source	LED lamp
Light Source Included	Yes
External Wiring	Cable 400 mm
Type of Connection	Plug 3-pole / 5-pole
Mounting Type	Brackets
IP Class	IP20
Ambient Temperature in °C	-25 ... +45
Cut Out in mm	95x95 / 95x187 / 95x 281 MM
Features	Different connectors

**Images**