



# DE38 S

Recessed mounted ceiling luminaire for accommodation and public areas

The **DE38S** from LightPartner is a recessed LED ceiling luminaire built for accommodation areas and public spaces. Its galvanized steel housing with a powder-coated finish ensures lasting durability, while the ice-crystal polycarbonate diffuser provides comfortable, glare-free illumination. Thanks to its practical clamp-mounting system, the DE38S can be installed quickly and securely in a wide variety of ceiling types, making it a highly adaptable solution for modern marine interiors. With options such as dimming, emergency backup, and alternative diffuser designs, it delivers reliable and versatile lighting tailored to demanding maritime standards.

## Technical Details

Possible combinations of features and other options available on request. Please contact us for more information.

Luminaire Type	Ceiling Luminaire
Input Voltage	230 VAC / 120 VAC / 120-230 VAC / 24 VDC
Area	Indoor
Application	Cruise / Offshore / Naval / Commercial
Frequency	50-60 Hz / 0 Hz
Wattage	2x 8 W / 2x 11 W
Lumen Output	1300 lm / 1850 lm
Color Temperature	3000 K / 4000 K / 5700 K / 6500 K / Red / Green / Blue
CRI Color Rendering Index	80 / 90
Control Mode	Switchable / Dimmable / DALI
Emergency Function	Sec. circuit / 3h Battery backup
Cover / Diffusor	Clear polycarbonate with ice crystal / prismatic / opal / parabolic louver

Material of Housing	Galvanized Steel
Color of Housing / Ring	RAL / NCS colors
Type of Light Source	LED
Light Source Included	Yes
Cable Entry	1-4x Grommets / 1-4x Cable glands M20, Plastic / Brass
External Wiring	Ø 6 - 13 mm
Type of Connection	Terminal 3-pole / 5-pole, 2.5mm <sup>2</sup> / 4mm <sup>2</sup>
Internal Wiring	Through wired
Mounting Type	Bracket
IP Class	IP20/44
IK Class	-20 ... +40 / -25 ... +45
Cut Out in mm	233x640 mm
Features	B0 Execution / Shock proof/ EMI proof

**Images**
