



DL170

Flat surface LED downlight for wall and ceiling mounting, with changeable cover ring of various colors

The **DL170** is a compact and elegant LED downlight designed for ceiling or wall installation. Its slim profile and decorative steel ring ensure a refined look, while the optimized optics provide a wide, homogeneous light distribution that enhances both functionality and atmosphere. Thanks to its shallow installation depth, it is ideal for confined spaces and easy to integrate into various interior concepts. The DL170 is available in different light colors and with optional emergency lighting versions, offering flexibility for diverse applications.

Technical Details

Possible combinations of features and other options available on request. Please contact us for more information.

Luminaire Type	Downlight
Input Voltage	230 VAC / 24 VDC
Area	Indoor
Application	Cruise / Offshore / Naval / Commercial
Frequency	50-60 Hz / 0 Hz
Wattage	1x 8 W
Lumen Output	450 lm
Color Temperature	2700 K / 3000 K / 4000 K
CRI Color Rendering Index	80 / 90
Control Mode	Switchable / Dimmable

Emergency Function	Optional Sec. circuit
Cover / Diffusor	Opal Polycarbonate
Material of Housing	Polycarbonate
Color of Housing / Ring	RAL / NCS colors / Chrome (has to be ordered separately)
Type of Light Source	LED
Light Source Included	Yes
Type of Connection	Contact plug via ceiling connector with plug 3-pole (has to be ordered separately)
Mounting Type	Mounting holes
IP Class	IP20
Ambient Temperature in °C	-25 ... +45
Features	B0 / B15 application

Images
