



DL63 IP55

LED Downlight with changeable cover ring, for cabins, accommodation and public areas

The **DL63 IP55** is a durable LED downlight designed for cabins, accommodation areas, and public spaces. Its galvanized steel housing with powder-coated finish and interchangeable cover rings allows seamless integration into various interiors. Offering multiple wattage options and warm, uniform illumination, it delivers flexible lighting solutions. Rated IP55, it is protected against dust and water, easy to install, and compliant with maritime classification standards. Optional features include dimming and emergency battery backup.

Technical Details

Possible combinations of features and other options available on request. Please contact us for more information.

Luminaire Type	Downlight
Input Voltage	230 VAC / 110 - 240 VAC / 24 VDC
Area	Indoor and Outdoor
Application	Cruise / Offshore / Naval / Commercial
Frequency	50-60 Hz / 0 Hz
Wattage	1x 5 W / 1x 10 W / 1x 20 W
Lumen Output	500 lm / 1000 lm / 2000 lm
Color Temperature	3000 K / 4000 K / 5700 K / 6500 K / Red / Green / Blue
CRI Color Rendering Index	80 / 90
Control Mode	Switchable / Dimmable / DALI
Emergency Function	Sec. circuit / 3h Battery backup
Cover / Diffusor	Glass satin

Material of Housing	Galvanized Steel
Color of Housing / Ring	RAL / NCS colors / chrome / brushed
Type of Light Source	LED
Light Source Included	Yes
Cable Entry	Optional
External Wiring	Cable 400 mm
Type of Connection	Plug 3-pole / 5-pole
Mounting Type	Mounting holes
IP Class	IP20/55
Ambient Temperature in °C	-25 ... +45
Cut Out in mm	143 mm
Features	Shock proof / EMI proof / Adaption light / Connection box

Images
